


Hot Water Washdown Spray Nozzles

Applications:

- for low pressure cleaning, tank and drum cleaning and chemical manufacturing

Features:

- designed for operator comfort
- variable spray pattern from conical spray to solid stream
- hose connects at base of gun for easy maneuvering
- ½" female NPT inlet
- rubber coated handle protects hands from water temperatures to 150°F
- 12.5 GPM flow capacity at 150 PSI
- Do not use with steam lines. 



| Cover Color | Brass | | Aluminum | |
|-------------|---------------|-----------------|---------------|-----------------|
| | Part # | Price/E | Part # | Price/E |
| black | BWSG | \$269.40 | AWSG | \$288.75 |
| white | BWSG-W | 295.95 | AWSG-W | 309.05 |

Swivel Connectors for Washdown Spray Guns

Ball Type Swivel x Hose Shank

Features:

- 300 series stainless steel swivel connector for stainless spray nozzles
- 360° ball type swivel adapter helps prevent hose kinking

| NPT | Hose ID | Part # | Price/E |
|-----|---------|--------------|-----------------|
| ½" | ½" | SSA44 | \$212.60 |
| ½" | ⅝" | SSA54 | 212.60 |
| ½" | ¾" | SSA64 | 212.60 |



Straight Swivel x Hose Shank

Features:

- swivel body
- EPDM gasket

| NPT | Hose ID | Brass | | Stainless Steel | |
|-----|---------|--------------|----------------|-----------------|----------------|
| | | Part # | Price/E | Part # | Price/E |
| ½" | ½" | BNS44 | \$61.90 | BNS44SS | \$81.40 |
| ½" | ¾" | BNS64 | 61.90 | BNS64SS | 110.45 |



Straight Swivel x GHT Thread

| NPT | Female GHT | Brass Part # | Price/E |
|-----|------------|----------------|----------------|
| ½" | ¾" | BMAS974 | \$61.90 |



Thermal-Gard™ Elevated Temperature Spray Nozzle

Features:

- Thermal-Gard™ elevated temperature spray nozzle protects the operator from extreme hot water temperatures that exceed the comfort zone of standard hot water nozzles.
- Assembly includes required special rigid, stainless steel adapter, (⅜" male NPT x ½" female NPT).
- Thermal insulating sleeve reduces overall heat during elevated temperature conditions.
- Stainless steel lever handle is coated for additional thermal protection and operator comfort.
- Lightweight aluminum alloy body reduces overall weight
- Aluminum alloy body is electroless nickel plated for additional corrosion protection
- Recommended for water temperatures above 140°F to a maximum temperature of 200°F.
- 12.5 GPM flow capacity
- working pressure: 150 PSI
- ⅜" female NPT inlet
- black cover



| Aluminum | |
|----------------|-----------------|
| Part # | Price/E |
| AWSG-TG | \$355.80 |