



FEATURES:

- Wall mounted
- Aerated, yellow plastic spray outlet, dust cap
- 3/8 in. NPT female brass, chrome-plated
- Self-closing valve
- Brass, chrome-plated squeeze handle activator
- 6 ft. reinforced hose, 750 PSI burst pressure, integral hanger for valve
- 3/8 in. NPT male inlet, swivel connection
- 1.5 gpm @ 30 psi

COMPLIANCE:

- All units meet existing ANSI Z358.1 1998 standards and OSHA rules for drench hoses

OPTIONS:

ADD SUFFIX TO MODEL #

- Vacuum breaker

-VB

WARRANTY:

- 3 year limited

SEE REVERSE FOR ROUGH-IN DIMENSIONS

THIS SPACE FOR ARCHITECT/ENGINEER APPROVAL.

SPEAKMAN®

400 ANCHOR MILL ROAD | NEW CASTLE, DE 19720
P: 800-537-2107 | F: 800-977-2747
WWW.SPEAKMANCOMPANY.COM

REVISION DATE: SEPTEMBER 2015



Management Systems
Registered to ISO 9001

SPEAKMAN[®]

Drench hose SE-920

SPECIFICATION

NOTE: 1. All dimensions are in inches (millimeters) unless otherwise specified and are subject to change without notice.

THIS SPACE FOR ARCHITECT/ENGINEER APPROVAL.

SPEAKMAN[®]

400 ANCHOR MILL ROAD | NEW CASTLE, DE 19720
P: 800-537-2107 | F: 800-977-2747
WWW.SPEAKMANCOMPANY.COM

Management Systems
Registered to ISO 9001

REVISION DATE: FEBRUARY 2015