8/11/2020 XtraExport

Spears® Technical Information

10-Aug-20 06:57:36 PM

| Desc: 2 TRUE LUG BUTTERFLY | | |
|---------------------------------------------|----------------------------------------------------|---------------------------------------------------|
| | ITH BASIC MANUAL OVERRIDE | |
| MSRP: 1468.92 | Part Code: 540 | |
| Weight(lbs): 6.354 | Weight(kg): 2.882 | Weight(gm): 2882 |
| Size: | Color: | Material: |
| | Connection Buna-N with Zinc Lugs | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| = | | |
| ection Molded Dimension Ref | | |
| = (LAYING LENGTH) intersection of inch. | of center lines to bottom of socket/th | read; 90° elbows, tees, crosses; ± 1 |
| = Intersection of center lines to face of | of fitting; 90° elbows tees, crosses; ± | 1/32 inch. |
| = Intersection of center lines to botto | m of socket/thread; 45° elbows; $\pm 1/3$ | 32 inch |
| = Overall length of fittings; $\pm 1/16$ in | ch. | |
| = Outside diameter of socket/thread h | nub; ± 1/16 inch. | |
| = Socket bottom to socket bottom; co | ouplings; ± 1/16 inch. | |
| = Height of cap; $\pm 1/16$ inch | | |
| | | |
| pical Molded Dimension Refer | <u>rences</u> | |
| | | |
| | | |
| | | |
| | | |
| | | |

The information printed here is based on current information & product design at the time of publication and is subject to change without notification. Spears® ongoing commitment to product improvement may result in some variation. No representation, guarantees or warranties of any kind are as to its accuracy, suitability for particular application or results to be obtained thereform. For verification of technical data or additional information, please contact Spears® Technical Service Department :: WEST COAST : (818) 364-1611 - EAST COAST : (717) 938-9006