8/11/2020 XtraExport

Spears® Technical Information

10-Aug-20 06:58:06 PM

art No: 51111H101-080	All	AV-1
		GS WITH DOUBLE ACTING 80PSI
MSRP: 3303.21	/ITH BASIC MANUAL OVERRI	art Code: 540
Veight(lbs): 34.696	Weight(kg): 15.738 Weight(gm): 15738	
Size:	Color:	Material:
) N 7 I
	Connection E	Buna-N with Zinc Lugs
=	e	
ection Molded Dimension Re		/dd- 000 -11 4 1 1
inch.	of center lines to bottom of socket	/thread; 90° elbows, tees, crosses; ± 1/
= Intersection of center lines to face	of fitting; 90° elbows tees, crosses	y = 1/32 inch.
= Intersection of center lines to botto	om of socket/thread; 45° elbows; ±	1/32 inch
= Overall length of fittings; $\pm 1/16$ in	nch.	
Outside diameter of socket/thread	hub; ± 1/16 inch.	
= Socket bottom to socket bottom; co	ouplings; ± 1/16 inch.	
= Height of cap; $\pm 1/16$ inch		
nical Molded Dimension Refe	rences	
= Height of cap; ± 1/16 inch (pical Molded Dimension Refe	rences	

The information printed here is based on current information & product design at the time of publication and is subject to change without notification. Spears® ongoing commitment to product improvement may result in some variation. No representation, guarantees or warranties of any kind are as to its accuracy, suitability for particular application or results to be obtained thereform. For verification of technical data or additional information, please contact Spears® Technical Service Department :: WEST COAST : (818) 364-1611 - EAST COAST : (717) 938-9006