8/11/2020 XtraExport

Spears® Technical Information

10-Aug-20 06:58:56 PM

ACTUATOR WITH BASIC MAN MSRP: 3515.56 /eight(lbs): 34.875 Size:	Weight(Co	(kg): 15.83 olor:		Weight	t(gm): 15819 terial:
/eight(lbs): 34.875	Co	(kg): 15.83 olor:	19	Weight Mat	terial:
	Co	olor:		Mat	terial:
Size:			Buna-N v		
	Сот	nnection	Buna-N v	vith Zinc Lug	gs
=					
ection Molded Dimension Refere	nces:				
= (LAYING LENGTH) intersection of ce inch.	enter lines to botto	om of sock	et/thread;	90° elbows,	tees, crosses; ± 1
= Intersection of center lines to face of fit	tting; 90° elbows	tees, cross	es; $\pm 1/32$	inch.	
= Intersection of center lines to bottom of	f socket/thread; 45	5° elbows;	± 1/32 inc	h	
= Overall length of fittings; $\pm 1/16$ inch.					
Outside diameter of socket/thread hub;	$\pm 1/16$ inch.				
= Socket bottom to socket bottom; coupli	$lngs; \pm 1/16 inch.$				
= Height of cap; ± 1/16 inch					
ical Molded Dimension Referen	<u>ces</u>				

The information printed here is based on current information & product design at the time of publication and is subject to change without notification. Spears® ongoing commitment to product improvement may result in some variation. No representation, guarantees or warranties of any kind are as to its accuracy, suitability for particular application or results to be obtained thereform. For verification of technical data or additional information, please contact Spears® Technical Service Department :: WEST COAST : (818) 364-1611 - EAST COAST : (717) 938-9006