8/11/2020 XtraExport

Spears® Technical Information

10-Aug-20 06:59:08 PM

| Desc: 10 TRUE LUG BUTTERFLY VALV | | ΓH AIR TO SPRING 80PSI |
|---|---|------------------------------------|
| ACTUATOR WITH BASIC MANUA | | . 540 |
| MSRP: 6469.71 | Part Code: 540 | |
| Weight(lbs): 69.053 | Weight(kg): 31.322 | Weight(gm): 31322 |
| Size: | Color: | Material: |
| | Connection Buna-N with Zinc Lugs | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| = | | |
| ection Molded Dimension Referenc | | |
| (LAVING LENGTH) intersection of cente | r lines to bottom of socket/thread | |
| inch | i fines to bottom of socker/timead | ; 90° elbows, tees, crosses; \pm |
| inch. | | |
| inch.Intersection of center lines to face of fitting | g; 90° elbows tees, crosses; ± 1/3: | 2 inch. |
| inch. Intersection of center lines to face of fitting Intersection of center lines to bottom of so | g; 90° elbows tees, crosses; ± 1/3: | 2 inch. |
| inch. Intersection of center lines to face of fitting Intersection of center lines to bottom of so Overall length of fittings; ± 1/16 inch. | g; 90° elbows tees, crosses; ± 1/32 in cket/thread; 45° elbows; ± 1/32 in | 2 inch. |
| inch. Intersection of center lines to face of fitting Intersection of center lines to bottom of so Overall length of fittings; ± 1/16 inch. Outside diameter of socket/thread hub; ± 1 | g; 90° elbows tees, crosses; ± 1/32 in cket/thread; 45° elbows; ± 1/32 in /16 inch. | 2 inch. |
| inch. Intersection of center lines to face of fitting Intersection of center lines to bottom of so Overall length of fittings; ± 1/16 inch. Outside diameter of socket/thread hub; ± 1 Socket bottom to socket bottom; couplings | g; 90° elbows tees, crosses; ± 1/32 in cket/thread; 45° elbows; ± 1/32 in /16 inch. | 2 inch. |
| inch. Intersection of center lines to face of fitting Intersection of center lines to bottom of so Overall length of fittings; ± 1/16 inch. Outside diameter of socket/thread hub; ± 1 Socket bottom to socket bottom; couplings | g; 90° elbows tees, crosses; ± 1/32 in cket/thread; 45° elbows; ± 1/32 in /16 inch. | 2 inch. |
| inch. Intersection of center lines to face of fitting Intersection of center lines to bottom of so Overall length of fittings; ± 1/16 inch. Outside diameter of socket/thread hub; ± 1 Socket bottom to socket bottom; couplings Height of cap; ± 1/16 inch | g; 90° elbows tees, crosses; ± 1/32 in cket/thread; 45° elbows; ± 1/32 in /16 inch. s; ± 1/16 inch. | 2 inch. |
| inch. Intersection of center lines to face of fitting Intersection of center lines to bottom of so | g; 90° elbows tees, crosses; ± 1/32 in cket/thread; 45° elbows; ± 1/32 in /16 inch. s; ± 1/16 inch. | 2 inch. |
| inch. Intersection of center lines to face of fitting Intersection of center lines to bottom of so Overall length of fittings; ± 1/16 inch. Outside diameter of socket/thread hub; ± 1 Socket bottom to socket bottom; couplings Height of cap; ± 1/16 inch | g; 90° elbows tees, crosses; ± 1/32 in cket/thread; 45° elbows; ± 1/32 in /16 inch. s; ± 1/16 inch. | 2 inch. |
| inch. Intersection of center lines to face of fitting Intersection of center lines to bottom of so Overall length of fittings; ± 1/16 inch. Outside diameter of socket/thread hub; ± 1 Socket bottom to socket bottom; couplings Height of cap; ± 1/16 inch | g; 90° elbows tees, crosses; ± 1/32 in cket/thread; 45° elbows; ± 1/32 in /16 inch. s; ± 1/16 inch. | 2 inch. |
| inch. Intersection of center lines to face of fitting Intersection of center lines to bottom of so Overall length of fittings; ± 1/16 inch. Outside diameter of socket/thread hub; ± 1 Socket bottom to socket bottom; couplings Height of cap; ± 1/16 inch | g; 90° elbows tees, crosses; ± 1/32 in cket/thread; 45° elbows; ± 1/32 in /16 inch. s; ± 1/16 inch. | 2 inch. |

The information printed here is based on current information & product design at the time of publication and is subject to change without notification. Spears® ongoing commitment to product improvement may result in some variation. No representation, guarantees or warranties of any kind are as to its accuracy, suitability for particular application or results to be obtained thereform. For verification of technical data or additional information, please contact Spears® Technical Service Department :: WEST COAST : (818) 364-1611 - EAST COAST : (717) 938-9006